

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 December 2004 (29.12.2004)


PCT

(10) International Publication Number  
**WO 2004/114479 A1**

- (51) International Patent Classification<sup>7</sup>: **H01S 3/081** (74) Agent: AWAPATENT AB; Box 45086, S-104 30 Stockholm (SE).
- (21) International Application Number: PCT/SE2004/001026 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 23 June 2004 (23.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0301812-4 24 June 2003 (24.06.2003) SE
- (71) Applicant (for all designated States except US): COBOLT AB [SE/SE]; Kräfttriket 8, S-104 05 Stockholm (SE). (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SPIEKERMANN, Stefan [DE/SE]; Tegvagen 10, S-175 53 Järfälla (SE).

[Continued on next page]

(54) Title: BEAM COMBINER



(57) Abstract: A laser arrangement with a resonant cavity which is folded by a folding mirror is disclosed. A quarter wave plate and retro-reflector are arranged outside one of the cavity mirrors. Frequency converted light that exits the cavity through this cavity mirror passes the wave plate twice before re-entering the cavity. In this way, light re-enters the cavity with a polarization direction that is orthogonal to its original polarization direction, and a combined, non-polarized output beam is obtained from the laser arrangement.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*